



seamaster
paint



ELASTIC *Klear*

ELASTOMERIC WATERPROOFING

transparent finish

For Exterior & Interior Use

Best used on Concrete, Metal, Wood and fences

Stay Klear Stay Sealed.

EFFLORESCENCE & ALKALINE RESISTANCE



UV RESISTANT & HARSH WEATHER TOLERANCE



SEAMLESS WATERPROOFING LAYER



PRODUCT DESCRIPTION

Seamaster Elastic Klear Elastomeric Waterproofing 8650 is formulated based on elastomeric modify acrylic copolymer for interior and exterior application. It is specially formulated to be excellent waterproofing, excellent UV resistance, with outstanding adhesion and harsh weather tolerance. Used to prevent water penetration into the substrates, prevent leakage, solve cracks on concrete that caused by rapid change of temperature.

PHYSICAL PROPERTIES

Dry Film Thickness	: 0.1 - 0.15mm	Recoating Interval	: 3 - 4 hours
Drying Time at (27 ± 2°C & RH : 80 ± 5%)	: Touch Dry ≤ 1 hour Hard Dry ≤ 3 hour	No. of Coats	: 2 - 3 coats
Theoretical Coverage	: 2.3 ~ 3.5m ² /kg (Actual coverage is dependent on substrate condition)	Method of Application	: Brush, Roller or Spray
		Finishing	: Clear

RECOMMENDED PLACE

*This product is not suitable to use in prolonged water immersion and water stagnant area. The areas should be in vertical



Window Sill



Brick wall



Metal Roofing



Concrete Roofing



Concrete Wall

SURFACE PREPARATIONS

New Surface

Let the concrete / plaster surface to dry out completely . It should be free from oil/grease and other contaminants.

Old Unpainted Surface

Surface should be dry and free from any structural damages. Wash out any stain, debris and powder-ness using high pressure water jet.

New / Previously Painted Metal Surface

Surface must be clean and dry free from dirt, mill scale, rust, grease, oil and loosed old paint. All should be removed

Previously Painted Surface

Remove the old paint by scraping or by brushing with a stiff brittle brush before the full painting work begins



Available in 1kg and 5kg

SEAMASTER PAINT GROUP



SEAMASTER PAINT (MALAYSIA) SDN. BHD. (101090-T)
SEAMASTER (MARKETING) SDN. BHD. (1292511-K)
 No. 32 & 34, Jalan Firma 2/1, Tebrau Industrial Estate 1, 81100 Johor Bahru, Johor, Malaysia
 Tel: 07-355 2088 Fax: 07-355 2081 Email: marketing@seamasterpaint.com.my
 www.seamasterpaint.com.my
 Johor • Juru • Kelantan • Melaka • Sabah • Sarawak • Shah Alam

SEAMASTER PAINT (S) PTE. LTD.
 Blk 421 Tagore Industrial Avenue #03-27, Singapore 787805
 Tel: +65 6265 1118 Fax: +65 6268 7796
 Email: spshq@seamaster.com.sg

SEAMASTER PAINT (VIETNAM) CO. LTD.
 16 Tu Do Avenue, VSIP, Thuan An, Binh Duong,
 Ho Chi Minh, Vietnam
 Tel: +84 2743 756118 Fax: +84 2743 756500
 Email: spvhq@seamasterpaint.com
 HCM City • Hanoi • Danang • Can Tho (Mekong)

SCAN ME FOR MORE INFORMATION

Discover More :

